



EVANS MACHINERY INC. 5530 N. 51<sup>ST</sup> AVENUE GLENDALE, ARIZONA 85301  
PHONE 623-934-7294 FAX 623-934-7384 WEB WWW.EVANSMACHINERYINC.COM  
PRICE LIST EFFECTIVE 5-1-2008

<b>0110</b>	<b>Post former 12' single sided with 90 degree forming leaf</b>	<b>13,850.00</b>
	Equipped with one - 90 degree leaf 220 Volt, 1 Ph., 14.5 kW or 380 Volt, 3 Ph. 50 Hz 100 PSI required Standard Features: Overhead radiant heater, with pneumatic controls and heat deflectors. Pneumatic controls on table and forming leaf. Solid steel frame with adjustable leveling feet. Steel constructed top platen for adjustable leaf spacing. (Adjusts for various size build up strips, ½ to 1 ½") Overhead heater, with vertical locking device. 35" working height Dimensions 175" long, 26" wide, 60" high Crated weight 1500 LBS. Shipping dimensions 182" long X 34" wide X 67" high <b>Options:</b> <b>Pneumatically operated cove rod system (required for doing a back splash)</b> <b>180 degree forming leaf</b> <b>Timer</b> <b>Extra 90 degree leaf</b>	<b>3,500.00</b> <b>2,550.00</b> <b>580.00</b> <b>1,650.00</b>
<b>0180</b>	<b>Degree Leaf, retrofit available for older models.</b> Call for quotation. Part # 0108-99-00-00	
<b>0138</b>	<b>All Form 8' capacity</b> 220 Volt, 1 Ph., 60 Hz, 20 amp. Or 380 Volt, 3 Ph. 50 Hz 100 PSI air required 1 CFM (2 CFM if using vacuum clamp) Standard Features: Hold down device: Over head clamp, Vacuum system Forming length capacity 100" 1 ½" maximum forming radius. (3" thick material) Foot print 4' wide X 11' long Thermostatically controlled heater, ambient to 500 degrees Fahrenheit Integrated timer. Individual control on all air components. Working height 36" Crated weight 1900 LBS. Shipping dimensions 145" long X 53" wide X 50" high	<b>23,150.00</b>
<b>0132</b>	<b>All Form 12' capacity</b> 220 Volt, 1 Ph., 60 Hz, 20 amp. or 380 Volt 3 Ph, 50 Hz. 100 PSI air required 1 CFM Standard Features: Hold down device: Over head clamp. Forming length capacity 145" 1 ½" maximum forming radius. . (3" thick material) Foot print 4' wide X 16' Long Thermostatically controlled heater, ambient to 500 degrees Fahrenheit Integrated timer. Individual control on all air components. Working height 36" Crated weight 2500 LBS. Shipping dimensions 182" long X 53" wide X 50" high	<b>32,700.00</b>
<b>0190</b>	<b>Pneumatic Cove Machine 12'</b> 220 Volt, 1 Phase 80 PSI Req. 12' Capacity Crated weight 1100 LBS. Shipping dimensions 182" long X 34" wide X 50" high	<b>7,980.00</b>

<b>6100</b>	<p><b>Form-O-Matic flow thru post former</b>                  220 Volt, 3 Ph., 60 Hz., or 380 Volt, 3 Ph., 50 Hz.                  17 kw (no air required) Standard work height 37".                  Standard Features:                  90 and 180 degree setup.                  Quick-change 90 and 180 degree roller assemblies each side.                  Maximum material width 48"                  Heaters: Infrared radiant panel (instant on / off)                  Foot print: 107"L X 72"W X 44"H, Work height 37"                  Maximum Feed rate 10 feet per minute.                  Feed motor: ½ hp variable speed DC drive.                  Crated weight 2400 LBS. Shipping dimensions 115" long X 80" wide X 55" high.</p>	<b>32,200.00</b>
<b>Options:</b>		
	<b>2 High Frequency motors for trimming 90 degree bends</b>	<b>5,990.00</b>
	<b>2 Conventional trimming routers</b>	<b>3,400.00</b>
	<b>40" work height</b>	<b>365.00</b>
	<b>Slitter motor with blade (for counter top operations)</b>	<b>3,770.00</b>
	<b>Bevel shape set-up part # 6100-01 (both sides)</b>	<b>800.00</b>
<b>0206</b>	<p><b>Pinch Roller 62" capacity with segmented bottom roller for countertop operation</b>                  115 Volt, 1 Phase, 100 PSI required                  Standard Features:                  45 lineal feet per minute, 30" working height                  Forward and reverse drive roller                  Safety gates on both in feed and out feed sides                  (Automatically raises top roller)                  Positive top roller adjustment                  Roll opening to 4". Please advise if running parts over 2"                  35 pounds per lineal inch at 100 PSI (48" material)                  Crated weight 740 LBS. Shipping dimensions 84" long X 33" wide X 57" high</p>	<b>5,400.00</b>
<b>0256</b>	<p><b>Pinch Roller 62" capacity with solid top and bottom rollers for flat panel laminating</b>                  Solid bottom roller                  115 volt, 1 phase, 100 PSI required                  Standard Features:                  45 lineal feet per minute                  30" working height                  Forward and reverse drive roller                  Safety gates on both in feed and out feed sides                  (Automatically raises top roller)                  Positive top roller adjustment                  Roll opening to 4". Please advise if running parts over 2"                  35 pounds per lineal inch at 100 PSI (48" material)                  Crated weight 740 LBS. Shipping dimensions 84" long X 33" wide X 57" high</p>	<b>5,300.00</b>
	<b>Options:</b>	
	<b>Variable speed control 0-90 ½ hp DC motor #01667</b>	<b>850.00</b>
	<b>Retro Fit Cylinder Guards 0206.11.00.00</b>	<b>260.00</b>
	<b>Riser base to 43"</b>	<b>295.00</b>
	<b>Riser base to 37"</b>	<b>245.00</b>
	<b>220 volt 1 phase 50hz</b>	<b>155.00</b>
<b>0366</b>	<p><b>Index Table for countertop fabrication using contact adhesive</b>                  80 PSI required                  Standard Features:                  Adjustments up to 61" wide                  Adjustable alignment of laminate to core stock                  Air pressure regulator, Pneumatically operated core positioning                  Shipped KD, Assembly required                  Crated weight 1000 LBS. Shipping dimensions 168" long X 25" wide X 24" high</p>	<b>5,270.00</b>
	<b>Riser base to 37"</b>	<b>245.00</b>

<b>0700</b>	<b>Mitre Saw, Manual Feed</b> 220 Volt, 3 Ph, 3 HP Standard Features: 16" Saw blade 1" arbor Set up for 90, 45, and 22 1/2 degree cuts Pneumatically operated SawGuard Double V belt Drive on arbor, Adjustable leveling feet. Swing out supports for longer lengths 60" X 96" working surface 4" dust outlet on back of dust hood 35 1/2 " working height 50" stroke Crated weight 1500 LBS. Shipping dimensions 108" long X 90" wide X 76" high	<b>9,250.00</b>
<b>0710</b>	<b>Mitre Saw, Power feed with variable speed control</b> Variable speed control 0-50 feet per minute, chain drive 220 Volt, 3 Ph., 3 HP Standard Features: 16" Saw blade 1" arbor Set up for 90, 45, and 22 1/2 degree cuts Pneumatically operated SawGuard Double V belt Drive on arbor Swing out supports for longer lengths 60" X 96" working surface 4" dust outlet on back of dust hood Built in over load protection Adjustable leveling feet. 35 1/2 " working height 50" stroke Crated weight 1500 LBS. Shipping dimensions 108" long X 90" wide X 76" high	<b>10,500.00</b>
<b>Options:</b>		
	<b>Pneumatic hold down device with 4 cylinders</b>	<b>1,650.00</b>
	<b>220 Volt 1 Phase</b>	<b>650.00</b>
	<b>380 Volt 3 Phase</b>	<b>915.00</b>
	<b>440 Volt 3 Phase</b>	<b>245.00</b>
	<b>Extra saw blade 08038</b>	<b>296.00</b>
	<b>Longer length's available</b>	<b>call for quotation</b>
	<b>Retrofit Saw Guard part # 0710-01</b>	<b>920.00</b>
	<b>5 HP 220 Volt 3 Phase</b>	<b>650.00</b>
<b>0750</b>	<b>Saw Carriage, without miter table or stand</b>	<b>6,450.00</b>
<b>0740</b>	<b>Saw Carriage, without miter table or stand. With power feed</b>	<b>7,700.00</b>
<b>1050</b>	<b>T-Edge Applicator</b> 220 volt, 1 Ph., 60 Hz. Or 220 Volt 1 Ph., 50 Hz. Standard Features: Hammer 1/2 hp motor Pneumatic corner notching Electric cutoff 1/2 hp motor 3" Dim. Saw blade 8,000 RPM 80 PSI Required Crated weight 500 LBS. Shipping dimensions 52" long X 40" wide X 48" high	<b>8,200.00</b>
<b>2470</b>	<b>OverArm Router</b> 110 Volt Standard Features: 3 HP router motor 80 PSI Required 21,000 RPM Working height 33" Includes router bit Part # 08018 cutting area 30" x 48" Lateral adjustment of pneumatic clamps. Crated weight 1010 LBS. Shipping dimensions 69" depth X 72" wide X 85" high	<b>6,480.00</b>

EVANS MACHINERY INC. 5530 N. 51<sup>ST</sup> AVENUE GLENDALE, ARIZONA 85301

PRICE LIST EFFECTIVE 5-1-2008

PAGE 4

<b>2480</b>	<p><b>OverArm Router</b>                      220 Volt, 3 Phase                      Standard Features:                      1.8 kW, 3 HP High frequency router motor                      80 PSI Required                      18,000 RPM                      Working height 33"                      Includes router bit Part # 08018                      cutting area 30" x 48"                      Crated weight 1500 LBS. Shipping dimensions 69" long X 72" wide X 65" high  <b>Optional: 440 Volt, 3 Ph., 80 PSI</b></p>	<p><b>11,000.00</b></p> <p><b>435.00</b></p>
<b>4253</b>	<p><b>Semi-automatic Index Table, for PVA panel laminating. Left to right feed</b>                      80 PSI Required.                      Standard Features:                      Max. Board size, 62" X 145"                      Min. Board size, 9" X 27"                      In feed height 43".                      Out feed height 40".                      Center conveyors supplied                      18" extensions on in feed side.                      Hand crank for width adjustment one revolution equals approx. 7".                      Adjustable guides for board positioning.                      Width opening indicator (scale with pointer)                      Width opening locking device, pneumatic break                      Heavy duty steel construction                      Adjustable leveling feet.                      Foot print, 87" X 169" plus 18" extensions                      Crated weight 1500 LBS. Shipping dimensions 174" long X 87" wide X 55" high  <b>Other than standard work height</b>  <b>Right to Left hand feed</b></p>	<p><b>16,900.00</b></p> <p><b>235.00</b>  <b>2,895.00</b></p>
<b>4243</b>	<p><b>Semi-automatic Index Table, for PVA cold press laminating. Left to right feed</b>                      80 PSI required                      Standard Features:                      Max. Board size, 62" X 145"                      Min. Board size, 9" X 27"                      In feed height 43".                      Out feed height 40".                      Open center for customer supplied scissors lift.                      18" extensions on in feed side.                      Hand crank for width adjustment one revolution equals approx. 7".                      Adjustable guides for board positioning.                      Width opening indicator (scale with pointer)                      Width opening locking device, pneumatic break                      Heavy duty steel construction                      Adjustable leveling feet.                      Foot print, 87" X 169" plus 18" extensions                      Crated weight 1500 LBS. Shipping dimensions 174" long X 87" wide X 55" high  <b>Other than standard work height</b>  <b>Right to left hand feed</b></p>	<p><b>16,900.00</b></p> <p><b>235.00</b>  <b>2,895.00</b></p>
<b>4270</b>	<p><b>Pneumatic Laminate Rack</b>                      100 PSI Required                      Max weight, 80 sheets 5' X 12' standard grade laminate.                      Dual level storage area                      Crated weight 1640 LBS. Shipping dimensions 81" long X 60" wide X 82" high</p>	<p><b>12,500.00</b></p>

<b>4603</b>	<p><b>Heat Tunnel, Continuous heated roller press.</b>                      Single Sided Laminator for panels and parts                      440 volt 3 phase, 100 PSI req.                      Standard Features:                      1-12 FT. per min.                      Max. Width 61"                      Max. Length unlimited, min. length 24"                      45 amp service                      3 sets silicon nip rollers with quick-change thickness adjustment                      Foot print 60" X 72" wide                      40" working height                      Crated weight 3000 LBS. Shipping dimensions 88" long X 74" wide X 68" high</p>	<b>38,210.00</b>
<b>4604</b>	<p><b>Heat Tunnel, Continuous heated roller press.</b>                      Double Sided Laminator for panels and parts                      440 volt 3 phase, 100 PSI req.                      Standard Features:                      1-12 FT. per min.                      Max. Width 61"                      Max. Length unlimited                      Min. length 24"                      60 amp service                      3 sets silicon nip rollers with quick-change thickness adjustment                      Foot print 60" X 72" wide                      40" working height                      Crated weight 3000 LBS. Shipping dimensions 88" long X 74" wide X 68" high</p>	<b>41,675.00</b>
	<p><b>Segmented rollers for counter top fabrication</b></p>	<b>6,100.00</b>
<b>4700</b>	<p><b>Panel Cleaner. Left to Right hand feed.</b>  <b>Riser Base</b>                      220 Volt 3 Phase                      Standard Features:                      30" Working Height                      4 each 6" dust collection outlets                      Powered in feed and out feed rollers                      In feed fence with extension to glue spreader.                      2 each 10" nylon brushes                      Roll opening indicator                      Emergency stop buttons and safety gate                      Custom designed hold down rollers move with upper brush                      1 ½ hp brush motor, ½ hp drive motor</p>	<b>17,430.00</b> <b>445.00</b>
<b>5010</b>	<p><b>Laminate Slitter, 6" capacity</b>                      110 Volt, 1 Ph., 1/3 HP,                      Standard Features:                      6" capacity                      Self feeds at 70 feet per minute                      3-blade system for inlay quality cuts                      Self-aligning fence                      Crated weight 240 LBS. Shipping dimensions 37" long X 24" wide X 29" high</p>	<b>3,200.00</b>
	<p><b>Optional 220 Volt 50 Hz (export)</b></p>	<b>210.00</b>
<b>5031</b>	<p><b>Laminate Slitter, 31" capacity</b>                      110 Volt, 1 Ph., 1/3 HP                      Standard Features:                      31" capacity floor model                      Self feeds at 70 feet per minute                      3-blade system for inlay quality cuts                      Self-aligning fence                      36" Working Height                      Crated weight 850 LBS. Shipping dimensions 72" long X 52" wide X 52" high</p>	<b>6,900.00</b>
	<p><b>Optional 220 Volt 50 Hz (export)</b></p>	<b>210.00</b>

PAGE 6

<b>6600</b>	<b>Double End Core Builder</b> 220 Volt 3 phase 60 cycle 30 amps. 100 PSI required Standard Features: 2 each 5 hp edge shaper with 1.25 spindles 20 feet per minute Board width maximum 48" minimum 16"; Board thickness maximum 2" Build up width maximum 1 1/2" minimum 3/4". Build up thickness 1 1/2" maximum	<b>68,770.00</b>
	<b>Hot Melt Station</b>	<b>19,700.00</b>
	<b>Dado Station for counter top operation</b>	<b>5,500.00</b>
	<b>T-Edge Slotter and applicator for no-drip edge</b>	<b>6,000.00</b>
<b>7300</b>	<b>Draw Bolt Pocket Cutter</b> 110 Volt, 60 Hz. , or 220 Volt, 1 Ph., 50 Hz., 80 PSI Standard Features: 1/2" Router Bit Aluminum. 4 position draw bolt template 90, 45, and 22 1/2 degree stops both right and left Pneumatic clamps Crated weight 200 LBS. Shipping dimensions 44" long X 35" wide X 22" high	<b>2,995.00</b>

### Contact Adhesive Spray Systems

<b>2 Gallon Setup</b>	<b>2,632.00</b>
Gun 63BSS Stainless Steel	
HAV-500 Metering Valve	
5/16 X 25' Air Hose	
3/8 X 25' Fluid Hose	
835-210 Pot Stainless Steel	
PT-78-K10 liners 10 each	
<b>5 Gallon Setup</b>	<b>3,204.50</b>
Gun 63BSS Stainless Steel	
HAV-500 Metering Valve	
5/16 X 25' Air Hose	
3/8 X 25' Fluid Hose	
835-510 Pot Stainless Steel	
PTL-408-K20 liners 20 each	